

E 12

12-CHANNEL MIXING CONSOLE WITH SUPERIOR EFFECTS AND EQs

DESCRIPTION

E 12 provides six studio-quality 54 dB gain range Mic preamps with combo connectors. Two line inputs are switchable to Hi-Z input. The input section also features three stereo line inputs and a stereo return. Input channels from 1 to 4 are equipped with a single-control compressor.

The six mono channels are provided with 3-band EQs, including shelving high and low bands and a semi-parametric mid-band with frequency selection and switchable Q choice, wide or narrow. The stereo input channels are provided with a three band EQ.



FEATURES

- 6 Mic/line in, 3 stereo line IN
- 1 Stereo return input
- 4 Single-control dynamic compressors (ch.1 - ch.4)
- 3 Band semiparametric EQ
- 3 Band EQ on stereo inputs
- 4 Aux sends per channel
- 60 mm progressive faders with dust cover
- 1 Stereo groups
- 32-Bit floating-point z.core dsp effects section

TECHNICAL SPECIFICATIONS

Electronic specifications	Frequency Response:	20 Hz ÷ 20 kHz
	THD+N, 20dB gain, 0dBu out	>0.02% A-Weighted
Inputs	Mic (Balanced XLR):	6
	Gain Range:	6 dB ÷ 60 dB
	Input Noise Level:	120 dBu A-Weighted
	Mic Input Impedance:	2 kohm
	Low Cut:	80 Hz
	Phantom Power +48V:	Yes
	Mono Line:	6
	Gain Selection:	-24 dB ÷ 30 dB
	Line Input Impedance:	60 kohm
	HI-Z Line Inputs:	2
	HI-Z Line Inputs Impedance (Mohm):	1 Mohm
	Stereo Line:	3
	Gain Selection:	-15 dB ÷ 15 dB
	Stereo Line Input Impedance (kOhm)	60 kohm
	Stereo Returns:	1
	Gain Selection	0 dB ÷ 10 dB
	Stereo Returns Input Impedance (kOhm)	60 kohm
	Outputs	Main MIX:
Control Room:		Yes
FX Send:		1
AUX Send:		4
AUX Output:		4
PHONES (6,8mm jack Stereo Line):		1
2 Track:		Yes
Outputs specifications	Output Impedance:	600 ohm
	Maximum Output Level:	22 dBu
	Aux Out Impedance (ohm):	600 ohm
	Aux Out Level:	22 dBu
	Group Out Impedance (ohm):	600 ohm
	Group Out Level:	22 dBu
	Phones Out impedance (ohm):	150 ohm
Compressors	RCF Compressors:	4 Single Control
EQ	Input Channels EQ:	1 Semi Parametric / 2 Shelving
	Description:	High Shelving at 10kHz +/-15dB Mid Semi parametric freq. 100Hz-8kHz, +/-15db, Wide/Narrow Q bell Low Shelving at 10Hz
Auxiliary sends	AUX:	2 PRE / 1 PRE/POST
	FX POST:	1



Internal Effects	Send Effects:	1
USB audio	Type:	B
	Play trk:	2
	Rec trk:	2
	Supported Play Formats:	WAVE
	Supported Rec Format:	WAVE
Other features	Footswitch:	Yes
Electrical specifications	Power supply:	Internal
	Voltage requirements:	90 V - 240 V
	Power consumption (MAX):	70 W
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Metal
Size	Height:	125 mm / 4.92 inches
	Width:	430 mm / 16.93 inches
	Depth:	385 mm / 15.16 inches
	Weight:	6.9 kg / 15.21 lbs
Shipping informations	Package Height:	215 mm / 8.46 inches
	Package Width:	580 mm / 22.83 inches
	Package Depth:	506 mm / 19.92 inches
	Package Weight:	8 kg / 17.64 lbs

PART NUMBER

- **17140108**

E 12

JP

EAN 8024530017033

- **17140086**

E 12

EAN 8024530015183

- **17140107**

E 12

UK





EAN 8024530017026

- **17140106**

E 12

US

EAN 8024530017019



VISTA 3D / 3D VIEW



MIXER E 12 90-240 V

REV.
A



ACCESSORIES