OUT OF STOCK

PowerLite 2155W Wireless WXGA 3LCD Projector

Contact Us 800.463.7766

Mon-Fri 7am-4pm PT



The bright, wireless WXGA projector with advanced security features.

The bright, feature-packed PowerLite 2155W portable projector brings brilliant widescreen performance to nearly any conference room or classroom, with native WXGA resolution for displays up to 300", plus robust wireless networking. Offering high Color Brightness[†], Epson® 3LCD projectors ensure bright, vivid images. With 5,000 lumens of color brightness and 5,000 lumens of white brightness¹, the 2155W shines bright in a variety of lighting conditions. And, it features great contrast for clear, impactful presentations. This powerhouse projector also includes enterprise-level wireless security for added peace of mind, as well as remote management and control of Epson networked projectors.

Projection System: High-aperture Epson 3LCD, 3-chip technology

Native Resolution: WXGA resolution (1280 x 800)

Color Brightness: 5000 lumens¹
White Brightness: 5000 lumens¹

Throw Distance Calculator

Model: V11H818020

\$1,699.00

Write a review

Overview

Bright and Colorful

Features 5000 lumens of color brightness (color light output)¹ and 5000 lumens of white brightness (white light output)¹.

Wireless Ready

Includes a high-speed LAN module for wireless connectivity

HDMI / MHL Connectivity

Stream 1080p content and mirror your mobile device with MHL & the latest in connectivity. Get instant access to movies, games and more from MHL-enabled devices.

Auto Screen Fit

Easily and quickly adjust the image to fit the screen.

WXGA Resolution

1280 x 800 HD widescreen resolution

- Far more accurate color with Epson 3LCD, 3-chip technology for high Color Brightness[†] and wide Color Gamut²
- Look for two numbers
 - o 5,000 lumens² Color Brightness for more accurate, vivid color
 - o 5,000 lumens² White Brightness for well-lit rooms
- Bright, widescreen images up to 300" WXGA resolution (1280 x 800); 16:10 performance
- Remarkable sharpness and detail 15,000:1 contrast ratio; added clarity when displaying text and graphics
- Robust integrated wireless networking enterprise-level security for peace of mind; compatible with WEP, WPA, WPA2-PSK and WPA2-EAP security protocols
- Split Screen³ feature simultaneously project two images (video or still) side-by-side from two different sources
- Remote management and control tools included software allows for remote monitoring and control of Epson networked projectors; also compatible with Crestron® RoomView®
- Long-lasting lamp up to 10,000 hours in ECO Mode⁴
- Versatile, compact design includes multiple connectivity options; ideal for taking from room to room or installing in small- to medium-sized spaces

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ▶

Specifications

Specifications Projector:

Projection System:

3LCD, 3-chip technology

Projection Method:

Front/rear/ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

1,024,000 dots (1280 x 800) x 3

Color Brightness - Color Light Output:

5,000 lumens

White Brightness - White Light Output:

5,000 lumens

Aspect Ratio:

16:10

Resolution:

1280 x 800 (WXGA)

Supported Resolution:

1920 x 1080 (1080p)

Resize:

640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050

Lamp Type:

300 W UHE

Lamp Life:

Up to 10,000 hours (ECO Mode), Up to 5,000 hours (Normal Mode)

Throw Ratio Range:

1.38 (Zoom: Wide), 2.24 (Zoom: Tele)

Size - projected distance:

29" - 280" (1.40 m - 13.71 m) (Zoom: Wide)

Keystone Correction:

Vertical: ± 30 degrees, Horizontal: ± 20 degrees

USB Plug 'n Play:

Projector is compatible with PC and Mac® computers

Contrast Ratio:

Up to 15,000:1

Color Reproduction:

Up to 1.07 billion colors

General:

Operating Temperature:

41 ° to 95 °F (5 ° to 35 °C)

Weight:

9.5 lb (4.3 kg)

Security:

Kensington-style lock provision

Projection Lens:

Type:

Optical Zoom (Manual)/Focus (Manual)

F-number:

1.5 - 2.0

Focal Length:

18.2 - 29.2 mm

Zoom Ratio:

1.0 - 1.6

Projector Details:

Input Signal:

Auto, RGB, and Component

Interfaces:

- 2x HDMI® (1 in common with MHL®)
- Computer: 1x D-sub 15 pin
- Video: 1x RCA
- · Audio-in: 3x Mini stereo
- Audio-in: 1x RCA (L & R)
- Network: 1x RJ-45, 100
- Mbps Serial: 1x RS-232c
- Monitor Out: 1x D-sub 15 pin

Speaker:

16 W (mono)

Fan Noise:

39 dB (Normal Mode), 29 dB (ECO Mode)

Projector Dimensions:

Including feet:

14.85" x 11.48" x 4.56" (W x D x H)

Excluding feet:

14.85" x 11.46" x 3.98" (W x D x H)

Remote Control:

Features:

Brightness, Contrast, Tint, Saturation, Sharpness, Input signal, Sync, Tracking, Position, Color temperature, Volume

Operating Distance:

26.2 ft (8 m)

Operating Angle:

Right/left: ± 45 degrees, Upper/lower: +45 to -15 degrees

Power:

Power Consumption:

- 429 W (Normal Mode)
- 340 W (ECO Mode)
- 2.0 W Standby (Communication On)
- 0.21 W Standby (Communication Off)

© 2020 Epson America, Inc.