

OUT OF STOCK

PowerLite X49 3LCD XGA Classroom Projector with HDMI

Contact Us 800.463.7766

Mon-Fri 7am-4pm PT



Encourage collaboration in the classroom with this versatile, 3LCD projector.

Create engaging classroom displays with the dynamic PowerLite X49 projector. Offering advanced 3LCD technology, this ultra bright projector delivers eye-catching, 3,600-lumen¹ displays with native XGA resolution. Designed to enhance in-class collaboration, the PowerLite X49 projects from smart devices and laptops², and features a built-in Moderator function that allows up to 50 users to connect to the display simultaneously³. Built to last, this durable projector provides a long lamp life of up to 12,000 hours in ECO Mode⁴, plus HDMI connectivity and convenient positioning flexibility for easy projection from anywhere in the classroom.

- 3,600 lumens of color and white brightness¹
- Native XGA resolution and 4:3 performance
- Long lamp life up to 12,000 hours in ECO Mode⁴
- Built-in Moderator function³ for easy sharing
- Advanced network connectivity
- **THROW DISTANCE AND DISPLAY SIZE CALCULATORS ►**

Model: V11H982020

OUR PRICE :

\$419.00[Write a review](#)

Overview

3-chip 3LCD technology for Best-in-Class Color Brightness⁵

3,600 lumens of color and white brightness¹

Native XGA resolution and a 4:3 aspect ratio for vibrant, colorful images

Low-priced, long-lasting lamp up to 12,000 hours in ECO Mode⁴

Moderator function³

allows up to 50 users to connect to the display simultaneously; perfect for displaying a variety of content or comparing students' work side-by-side

Advanced network connectivity

RJ-45 allows remote network projector management, presentations over the network, and more

Project from laptops and mobile devices

wirelessly display from PC, Mac®, Chromebook™, iOS® and Android™ devices²

- **Easy setup and positioning flexibility** — offers 1.2x optical zoom, ±30 degrees horizontal and vertical keystone correction, and Quick Corner®
- **HDMI connectivity** — get HD-quality video and audio with a single cable
- **Built-in 5 W speaker** — for engaging projector displays
- **Screen size up to 300"** — with Split Screen⁶ capability for side-by-side viewing

Eco Features

- RoHS compliant
- Recyclable product⁷
- Epson America, Inc. is a SmartWay™ Transport Partner⁸

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ►

What's In The Box:

- PowerLite X49 Projector

- Power cord
- Computer cable (VGA)
- Projector remote control
- Batteries
- Software CD
- Quick setup sheet
- Warranty card

Specifications

Specifications Projector:

Projection System:

3LCD, 3-chip technology

Projection Method:

Front / rear / ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

786,432 dots (1024 x 768) x 3

Color Brightness - Color Light Output:

3600 lumens¹

White Brightness - White Light Output:

3600 lumens¹

Aspect Ratio:

4:3

Resolution:

1024 x 768 (XGA)

Resize:

640 x 480 (VGA), 800 x 600 (SVGA), 1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1366 x 768 (WXGA60-3), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1680 x 900 (WXGA++), 1600 x 1200 (UXGA60)

Lamp Type:

210 W UHE

Lamp Life:

- ECO mode: Up to 12,000 hours⁴
- Normal mode: Up to 6,000 hours⁴

Throw Ratio Range:

1.48 (Zoom:Wide), 1.77 (Zoom:Tele)

Size - projected distance:

30" to 300" (0.89 to 9.12 m) (Zoom:Wide)

Keystone Correction:

- Vertical: ±30 degrees (Automatic)
- Horizontal: ±30 degrees (Slider)

USB Plug 'n Play:

Projector is compatible with PC and Mac® computers

Contrast Ratio:

Up to 16,000:1

Color Processing:

10 bit

Color Reproduction:

Up to 1.07 billion colors

General:

Temperature:

41° to 95° F (5° to 35° C)

Weight:

5.95 lb (2.7 kg)

Security:

- Kensington®-style lock provision
- Padlock
- Security anchor bar

Power:

Power Supply Voltage:

100 – 240VAC ±10%, 50 / 60Hz AC

Power Consumption:

- ECO mode: 235 W
- Normal mode: 345 W
- Communication on: 2.0 W Standby
- Communication off: 0.3 W Standby

Projection Lens:

Type:

Manual focus

F-number:

1.49 – 1.72

Focal Length:

16.9 mm – 20.28 mm

Zoom Ratio:

1.0 – 1.2

Remote Control:

Features:

A/V Mute, Freeze, Split, Aspect, Color Mode, Auto, MHL Menu, Volume

Operating Distance:

19.7' (6 m)

Operating Angle:

- Right / Left: ± 30 degrees
- Upper / Lower: ± 15 degrees

Projector Dimensions:

Including feet:

11.8" x 9.8 x 3.6" (W x D x H)

Excluding feet:

11.6" x 10.2" x 3.4" (W x D x H)

Projector Details:

Display Performance:

- NTSC: 480 lines
- PAL: 576 lines
(Depends on observation of the multi-burst pattern)

Input Signal:

NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM

Interfaces:

- 1x USB-A
- 1x USB-B
- 1x LAN
- 1x HDMI
- 2x Computer/Component
- 1x Video
- 1x RS-232c
- 1x Stereo Mini-jack (Mic)
- 1x Monitor Out
- Audio 1 & 2
- Audio L & R
- 1x Audio Out
- Wireless LAN port: 802.11 b/g/n (optional – module sold separately)

Speaker:

16 W (mono)

Fan Noise:

- ECO mode: 28 dB
- Normal mode: 37 dB

Eco Features:

- RoHS compliant
- Recyclable product⁷
- Epson America, Inc. is a SmartWaySM Transport Partner⁸

© 2020 Epson America, Inc.