

# Pro L1060WNL WXGA 3LCD Laser Projector

---



## Premium, compact large-venue laser projector.

The powerful Pro L1060WNL, part of Epson's most compact interchangeable-lens laser projector series, offers 3-chip 3LCD technology and native WXGA resolution for widescreen images, all in a sleek white casing. Delivering extraordinary color brightness, Epson® 3LCD projectors ensure brilliant images. Providing 6,000 lumens of color brightness and 6,000 lumens of white brightness<sup>1</sup>, the L1060WNL's laser light source and air filter offer virtually maintenance-free operation up to 20,000 hours<sup>2</sup>. With a high contrast ratio and BT.709 color space, it produces sharp, true-to-life images. And, it offers 11 interchangeable lens options (lens not included).

Some lenses will not support the maximum brightness level of this projector. [VIEW THE PDF](#) ►

**Model:** V11H958920

✉ Mail-in Rebate: Free Projector

## Overview

Ultra bright  
6,000 lumens color/white  
brightness<sup>1</sup> from a compact large-

Exceptional widescreen  
display

Vibrant, true-to-life  
images

venue laser projector

native WXGA resolution for  
widescreen images; provides up  
to 1 million pixels on screen

with Epson 3-chip 3LCD  
technology

### Worry-free operation

solid-state laser light source and  
air filter provide virtually  
maintenance-free operation for up  
to 20,000 hours<sup>2</sup>

### 11 optional interchangeable lenses

with powered lens shift and lens  
memory, including an ultra short-  
throw lens with zero offset (lens  
not included)

### Lifelike images

high contrast ratio and BT.709  
color space for exceptional clarity  
and detail

- **Dynamic projection capabilities** — advanced built-in Edge Blending, image warping and shape overlay features for a variety of applications; direct playback from USB storage media
- **Simplified installation features** — full 360-degree mounting, wide lens shift, versatile connectivity; inputs including HDBaseT™ and HDMI® (HDCP 2.2)
- **Customized performance** — brightness modes to maximize light source life and provide a consistent brightness level
- **Multi-projector setup software** — free software controls networked projectors and gives access to warping and edge blending
- **Web- or network-based remote management** — control and monitor projector status

## Eco Features

- RoHS compliant
- Recyclable product<sup>3</sup>
- Epson America, Inc. is a SmartWay™ Transport Partner<sup>4</sup>

### Better Products for a Better Future™

For more information on Epson's environmental programs, go to [www.epson.com/environment](http://www.epson.com/environment)

## What's In The Box:

- Pro L1060WNL projector
- power cable
- cable cover
- projector remote control with batteries
- Quick Setup Sheet

## Specifications

## Specifications Projector:

### Projection System:

High-aperture Epson® 3LCD, 3-chip technology

**Projection Method:**

Front/rear/ceiling mount

**Driving Method:**

Poly-silicon TFT Active Matrix

**Resolution on Screen:**

WXGA up to 1.0 million pixels

**Pixel Number in Device:**

1,024,000 pixels (1280 x 800) x 3 chips

**Signal Input:**

Maximum display resolution 1920 x 1080 (resizing display)

Display resolution 1280 x 800 pixels

**Color Brightness - Color Light Output:**

6,000 lumens<sup>1</sup>

**White Brightness - White Light Output:**

6,000 lumens<sup>1</sup>

**Aspect Ratio:**

Supports 4:3, 16:9, 16:10

**Brightness Uniformity:**

85%

**Pixel Arrangement:**

Cross stripe

**Keystone Correction:**

Vertical: ±45 degrees; horizontal: ±30 degrees

**Contrast Ratio:**

2,500,000:1 (Dynamic Contrast: On)

**Color Reproduction:**

Up to 1.07 billion colors

**Light Source Life:**

20,000 hours (Normal)<sup>2</sup>

**Illumination Technology:**

Laser Phosphor

**General:**

---

**Operating Temperature:**

32 ° to 113 ° F (0 ° to 45 ° C)

**Weight:**

34.4 lb without lens

**Security:**

Security cable hole, Kensington lock provision

**Projection Lens:**

---

**Type:**

Powered shift/focus/zoom (ELPLM08 Lens)

**F-number:**

1.7 – 2.3 (ELPLM08 Lens)

**Focal Length:**

24.0 mm – 38.2 mm (ELPLM08 Lens)

**Zoom Ratio:**

Optical zoom 1 – 1.6x (ELPLM08 Lens)

**Throw Ratio Range:**

1.44 – 2.32 (ELPLM08 Lens)

**Lens Shift:**

Vertical:  $\pm 67$  percent; Horizontal:  $\pm 30$  percent (ELPLM08 Lens)

## Projector Details:

---

**Input Signal:**

Input Video Signal (HDMI, DVI-D and HDBaseT ports) 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/ 4096 x 2160

**Interfaces:**

- DVI-D x 1
- HDMI (HDCP 2.2) x 1
- HDBaseT x 1
- 5-BNC, VGA x 1
- Audio in: Mini Stereo x 3
- Variable audio out: Mini Stereo x 1
- USB connector Type B x 1: For service only
- USB connector Type A x 1: For wireless LAN, service, content playback
- Monitor out: Mini D-sub 15-pin x 1
- Serial: RS-232c x 1
- Remote Stereo Mini x 1
- Wired LAN: RJ45

**Fan Noise:**

34 dB (Normal Mode); 32 dB (Medium Mode) 30 dB (Quiet Mode)

## Projector Dimensions:

---

**Including feet - with standard lens:**

21.5" x 7.4" x 19.1" (545 x 189 x 484 mm)

## Remote Control:

---

**Features:**

Power, source search selection, lens shift, zoom, focus, test pattern selection, A/V Mute, freeze, user ID, auto, aspect, color mode, number, page up and down, E-zoom, volume, menu, enter, esc and pointer functions

**Operating Distance:**

98 ft

**Operating Angle:**

- Right/left: Front:  $\pm 60$  degrees; Rear:  $\pm 30$  degrees

- Upper/lower: Front: + 30 to - 20 degrees; Rear: +50 to + 10 degrees

## Power:

---

### Power Supply Voltage:

100 – 240 V  $\pm$ 10%, 50/60 Hz AC

### Power Consumption:

361 W (Normal Mode), 263 W (Extended Mode), 2W (Network Standby), 0.5 W (Energy Saving)

---

© 2020 Epson America, Inc.