



- The device is designed to operate in a temperate environment, with a correct Operating Temperature of 0–50° C, 32–122° F.

TECHNICAL SPECIFICATIONS

Satori

✓ ✓ Analog Inputs

4 x Stereo Pair Line Level Inputs. Ch1 on XLR & Ch2–4 on TRS
4 x Stereo Line Level Inputs on D-Sub 25
1 x Talkback Mic Preamp on TRS

✓ ✓ Analog Outputs

4 x Stereo Line Level Outputs on D-Sub 25
4 x Stereo Pair Monitor Outputs, Mon1 on XLR and Mon2–4 on TRS
1 x Line Level Stereo Sum Output on TRS
1 x LFE Output on TRS
4 x Headphone Outputs (two on the rear and two on the front) on TRS

✓ ✓ USB I/O

USB 2.0 Hi-Speed, Type B
For use with the software control panel

✓ ✓ Dynamic Range

132dB

✓ ✓ THD + N

127dB

✓ ✓ Operating temperature

0–50° C / 32–122° F

✓ ✓ Weight

~2kg / 4,4lb approx.

✓ ✓ Dimensions

Width: 483 mm / 19" /Rack/
Height: 44 mm(1U) / 1,75"
Depth: 220 mm / 8,66"

✓ ✓ Power Supply

AC Universal input ~95–245 V

✓ ✓ Power Consumption

25 Watts Max.

R4S

USB: USB 2.0 Full-Speed interface on USB Type B connector

Operating Temperature: 0–50°C, 32–122° F

Weight (unit): 0.71 kg, 1.57 lb

Dimensions (unit): 220 mm(W) x 55 mm(H) x 85 mm(D), 8.66"(W) x 2.22 "(H) x 3.31"(D)