

CHRISTIE HS SERIES D13WU-HS / D13HD-HS

Enterprise venues and boardrooms | Entertainment venues | Fixed installation | Houses of worship
Hotels | Live events and conferences | Rental and staging | Trade shows and exhibitions

Brilliant colors at a brilliant price

When color accuracy and affordability are key, choose the Christie® D13WU-HS or D13HD-HS 1DLP® laser projector. Producing 13,000 lumens, HD or WUXGA resolution and featuring patented Christie BoldColor™ Technology, visuals are vibrant and true to life when compared to standard laser phosphor projectors.

With built-in, camera-based warping and blending, these projectors are easy to set up, whether on their own or as part of a multi-projector array. Their compact and lightweight form factor, omnidirectional capabilities, and optional rigging frame make the D13WU-HS and D13HD-HS perfect options for challenging installation spaces.



CHRISTIE®

Technical specifications

Christie D13WU-HS

Christie D13HD-HS

Image	brightness (lumens)	• 13,500 ISO • 12,500 Center • 12,000 ANSI	• 13,000 ISO • 12,000 Center • 11,500 ANSI
	color wheel	• 4 segment (RGBY) - 2X or 3X speed	
	contrast	• Full on/off (Christie RealBlack™ enabled): 750,000:1 • Dynamic contrast: 7500:1 (WU), 6500:1 (HD) • Full on/off (Christie RealBlack disabled): 1200:1 • 250:1 ANSI	
Display technology	type	• 1 x 0.96" DMD	• 1 x 0.95" DMD
	native resolution	• 1920 x 1200 (2,304,000 pixels) 16:10	• 1920 x 1080 (2,073,600 pixels) 16:9
Illumination	type	• Laser phosphor with Christie BoldColor™ Technology	
	typical lifetime	• 20,000 hrs	
Signal inputs	standard	• HDMI x 2 (one on rear panel, one on bottom of projector, independently selectable) • 3GSDI x 1 (BNC) • DVI-D x 1 (digital only) • HD15 x 1 • USB x 1 (Type B mini) • Display over USB • HDBaseT (RJ45 x 1) • USB x 1 (Type A) • Image Viewer or Wi-Fi® dongle (optional) • RJ45 x 1 (Christie Presenter over wired network connection)	
	signals	• HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio, all inputs	
	3D	• HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side (up to 120Hz output) • 3D sync in (BNC) - for genlocking projectors • 3D sync out (BNC) - for genlocking projectors, or controlling emitter or polarizer	
	scan rates	• Horizontal: 15kHz to 91kHz • Vertical: 24Hz to 85Hz	
Signal outputs		• 3GSDI x 1 (BNC) • DVI-D x 1 (digital only)	
Control and networking		• RS-232 in • Control via HDBaseT • Ethernet (100BaseT) RJ45 with ChristieNET™ connectivity • Built-in backlit keypad • Wired remote control (3.5mm stereo) • Loop out available for daisy chaining	
Lenses	mount type	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)	
	lens options	• 0.84-1.02:1 zoom lens (no zoom/focus memory) • 1.02-1.36:1 zoom lens (no zoom/focus memory) • 1.2-1.5:1 zoom lens (full ILS) • 1.5-2.0:1 zoom lens (full ILS) • 2.0-4.0:1 zoom lens (full ILS) • 4.0-7.0:1 zoom lens (full ILS)	
	offsets for full ILS lenses	• ±120% Vertical (±720 pixels) • ±50% Horizontal (±480 pixels)	• ±133% Vertical (±720 pixels) • ±50% Horizontal (±480 pixels)
	offsets for 0.84-1.02:1	• +37/-60% Vertical (+222/-363 pixels) • +15/-44% Horizontal (+152/-426 pixels)	• +110/-86% Vertical (+596/-466 pixels) • +34/-39% Horizontal (+330/-376 pixels)
	offsets for 1.02-1.36:1	• +51/-53% Vertical (+307/-318 pixels) • +11/-50% Horizontal (+107/-480 pixels)	• +125/-98% Vertical (+676/-534 pixels) • +42/-47% Horizontal (+408/-457 pixels)
Accessories	standard	• IR remote w/wired remote jack (wire not included) • AC line cord for projector head • User manual	
	optional	• Christie One Rigging Frame • Lens adapter for E Series lenses • 1DWUSB-BGN (wireless dongle for video and control) • Christie HS Series fog filter refills (1 set) • Christie HS Series fog filter covers and filters (order once per projector then only filter refills) • Christie One Mount Plus • One Mount Extender Rod • Replacement remote control • One Mount Rigging Kit (used with One Mount, One Mount Plus and/or One Mount Extender Rod)	
Power requirements	operating voltage	• Normal: 100-120 VAC/200-240 VAC; 60/50Hz	
	power consumption	• Normal mode: 1220W ±15% (200 VAC), 1300W ±15% (100 VAC) • ECO1 mode: 1000W ±15% (220 VAC), 1050W ±15% (100 VAC) • ECO2 mode: 660W ±15% (220 VAC), 700W ±15% (100 VAC)	
	operating current	• Normal mode: 7A (200-240 VAC), 14A (100-120 VAC)	
	dissipation	• Normal mode: 4435 BTU/hr • ECO1 mode: 3580 BTU/hr • ECO2 mode: 2390 BTU/hr	
Audible noise		• Typical: 39dBA • Eco mode: 37dBA	
Physical	size	• (L xWxH) 26.65 x 23.46 x 7.99" (677 x 596 x 203mm) w/o feet	
	shipping size	• (L xWxH) 36.4 x 33.3 x 20.2" (925 x 845 x 515mm)	
	weight (w/o lens)	• 93.7lbs (42.5kg)	
	shipping weight	• 127lbs (57.5kg)	
Operating environment	temperature	• 32-104°F (0-40°C)	
	humidity	• 0-85% non-condensing	
Regulatory		• Contact Christie for the timing of certifications: UL/CSA/IEC 60950-1, FCC Class A, CE, FDA, CCC, KC, PSE, CU, SABS, BIS, VCCI, RCM, Ukr, TER, SASO • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • RoHS, REACH, WEEE	
Warranty		• Three years parts and labor on the projector • Three years or 15,000 hours parts and labor on the illumination system ¹ • Contact an authorized Christie representative for full details of our limited warranty	

¹ Please reference Christie Standard Limited Warranty document for details.

For the most current specification information, please visit christiedigital.com



Copyright 2019 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. 4693 Nov 19



CHRISTIE