

CHRISTIE HS SERIES D16WU-HS / D16HD-HS

Auditoriums | Enterprise venues and boardrooms | Entertainment venues | Houses of worship
Hotels | Live events and conferences | Rental and staging | Trade shows and exhibitions

Power is freedom.

Enjoy the freedom of unrestricted power. Hitting 16,000 lumens, the Christie® D16WU-HS and D16HD-HS are the lightest and brightest 1DLP® laser projectors to operate at full-brightness on a single 12A, 120V circuit. There's no need for high-power runs. Simply plug it into a standard 120V outlet and start the show!

Visuals are stunning thanks to the enhanced color accuracy of Christie's patented BoldColor™ Technology and HD or WUXGA resolution.

The long-lasting and reliable laser light source and affordability of 1DLP technology means these projectors are a cost-effective option for high-use applications. With built-in Christie Twist™, users have the tools needed to quickly and easily set up and align irregular screens and multi-projector displays.

These projectors come with the option to add Christie Mystique® automated camera-based alignment software, letting you quickly stage, install, align, and recalibrate multi-projection systems in minutes.



CHRISTIE®

Technical specifications

Christie D16WU-HS

Christie D16HD-HS

Image	brightness (lumens)	<ul style="list-style-type: none"> • 17,400 ISO • 15,500 ANSI 	<ul style="list-style-type: none"> • 15,750 ISO • 14,000 ANSI
	color wheel	• 4 segment (RGBY) - 2X or 3X speed	
	contrast (nominal)	<ul style="list-style-type: none"> • Full on/off (Christie RealBlack™ enabled): 2,000,000:1 • Dynamic contrast: 6000:1 • Full on/off (Christie RealBlack disabled): 1200:1 • ANSI 250:1 	
Display technology	type	• 1 x 0.96" DMD	
	native resolution	• 1920 x 1200 (2,304,000 pixels) (16:10)	• 1920 x 1080 (2,073,000 pixels) 16:9
Illumination	type	• Laser phosphor with Christie BoldColor™ Technology	
	performance	• 20,000 hrs to 50% brightness	
Signal Inputs	standard	<ul style="list-style-type: none"> • HDMI x 2 (HDCP 2.2) (one on side panel, one on bottom) • 3GSDI x 1 (BNC) • DVI-D x 1 (digital only) • VGA x 1 • USB x 1 (Type A) • Wi-Fi® dongle (optional) • HDBaseT (RJ45) x 1 	
	signals	<ul style="list-style-type: none"> • HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio (all inputs) 	
	3D	<ul style="list-style-type: none"> • HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side (up to 120Hz output); frame sequential @ 1080P up to 120Hz. • 3D sync in (BNC) - for genlocking projectors • 3D sync out (BNC) - for genlocking projectors, or controlling emitter or polarizer 	
	pixel clock	• 162 MHz	
	scan rates	• Horizontal: 15-91kHz • Vertical: 24-120Hz	
Signal outputs	monitor out (loop-through)	• 3GSDI x 1 (BNC) • HDMI x 1 (HDMI out)	
Control and networking		<ul style="list-style-type: none"> • HDBaseT (RJ45 x 1) • RJ45 x 1 (Ethernet Control over wired network connection) • RS232 x 1 • Built-in backlit keypad • IR Remote • Remote in: 3.5mm stereo female (provides serial communications and power) • Loop out available for daisy chaining • DC JACK 12VDC, 200 mA. 	
Warping and blending	mount type	• Christie Twist™	
	optional	<ul style="list-style-type: none"> • Christie Twist Premium and Twist Pro • Christie Mystique® automated camera-based alignment 	
Lenses	mount type	<ul style="list-style-type: none"> • Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses) 	
	lens options	<ul style="list-style-type: none"> • 0.38:1 UST lens • 0.84-1.02:1 zoom lens (no zoom/focus memory) • 1.02-1.36:1 zoom lens (no zoom/focus memory) • 1.2-1.5:1 zoom lens (full ILS) • 1.5-2.0:1 zoom lens (full ILS) • 2.0-4.0:1 zoom lens (full ILS) • 4.0-7.0:1 zoom lens (full ILS) 	
	offsets for 0.38:1 UST lens	<ul style="list-style-type: none"> • +100/-55% Vertical • +4/-28% Horizontal 	<ul style="list-style-type: none"> • +120%/-65% Vertical • +7%/-15% Horizontal
	offsets for 0.84-1.02:1	<ul style="list-style-type: none"> • +108/-74% Vertical • +29/-42% Horizontal 	
	offsets for 1.02:1-1.36:1	<ul style="list-style-type: none"> • +124/-98% Vertical • +40/-49% Horizontal 	
	offsets for full ILS Lenses	<ul style="list-style-type: none"> • ±140% Vertical • ±50% Horizontal 	
Accessories	standard	<ul style="list-style-type: none"> • IR remote with wired remote jack (wire not included) • AC line cord for projector • Product Safety Guide 	
	optional	<ul style="list-style-type: none"> • Christie One Mount Plus (140-117100-XX) • One Mount Extender Rod (121-125109) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX) • Christie One Rigging Frame (140-113106-XX) • WiFi Dongle (133-113106-XX) • Fog Filter with Frame (003-005714-XX) • Fog Filter module (003-005715-XX) 	
Power requirements	operating voltage	• Normal mode: 120-240 VAC @ 50/60Hz with 15A fuse	
	power consumption	• Normal mode: 1410 W • Eco1 mode: 1150W Eco2 mode: 700W	
	operating current	• Normal mode: 7A (200-240VAC), 12A (120 VAC)	
	dissipation	• Normal mode: 4811 BTU/hr • Eco1 mode: 3924 BTU/hr • Eco2 mode: 2388 BTU/hr	
Audible noise		<ul style="list-style-type: none"> • Standard mode: 41dB(A) • Eco2 mode: 35dB(A) (2x wheel speed) • Standard mode: 42dB(A) • Eco2 mode: 37dB(A) (3x wheel speed) 	
Physical	size	• (L xWxH) 26.65 x 23.46 x 7.99" (677 x 596 x 203mm) w/o feet	
	shipping size	• (L xWxH) 37.99 x 31.30 x 14.37" (965 x 795 x 365mm)	
	weight	• 91.52lb (41.6kg)	
	shipping weight	• 117.7lb (53.3kg)	
Operating environment	temperature	• 32-104°F (0-40°C)	
	humidity	• 10-85% non-condensing	
Regulatory		<ul style="list-style-type: none"> • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • FCC Class A • cTUVus • CE • FDA • CCC • KC • PSE • EAC • BIS • VCCI • RCM • TER • Mexico • BSMI 	
Warranty		<ul style="list-style-type: none"> • Three years parts and labor on the projector • Three years or 15,000 hours parts and labor on the illumination system¹ • Contact an authorized Christie representative for full details of our limited warranty 	

¹ Reference the Christie Standard Limited Warranty document for details.

For the most current specification information, please visit christiedigital.com

Copyright 2020 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD1266 Apr 20



CHRISTIE®