

# Specifications

As of June, 2015

## General

Power:	DC 12 V (11.0 V to 17.0 V)
Power Consumption:	22 W (when the optional board AG-YA600G is installed)
Operating Temperature:	0°C to 40°C (32°F to 104°F)
Operating Humidity:	10% to 85% (relative humidity)
Storage Temperature:	-20°C to 60°C (-4°F to 140°F)
Weight:	Approx. 2.8 kg (6.2 lbs.) (body only, excluding the battery and accessories)
Dimensions:	144 mm (W) × 267 mm (H) × 350 mm (D) (5-21/32 inches × 10-1/2 inches × 13-25/32 inches) Body only, excluding protrusion

## Camera Unit

Pickup Device:	2/3 type 2.2 million pixels, MOS × 3
Lens Mount:	2/3 type bayonet
ND Filter:	1: CLEAR, 2: 1/4ND, 3: 1/16ND, 4: 1/64ND
Gain Setting:	NORMAL mode: -3 dB, 0 dB, 3 dB, 6 dB, 9 dB, 12 dB, 15 dB, 18 dB, 21 dB, 24 dB, 27 dB, 30 dB HIGH SENS mode: -6 dB, -3 dB, 0 dB, 3 dB, 6 dB, 9 dB, 12 dB, 15 dB, 18 dB, 21 dB, 24 dB, 27 dB, 30 dB
Super Gain (S.GAIN):	Selectable from 30 dB, 36 dB, 42 dB
Shutter Speed:	60i/60p mode: 1/60 (OFF) sec., 1/100 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 sec., 1/2000 sec. 30p mode: 1/30 (OFF) sec., 1/50 sec., 1/60 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 sec. 24p mode: 1/24 (OFF) sec., 1/50 sec., 1/60 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 sec. 50i/50p mode: 1/50 (OFF) sec., 1/60 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 sec., 1/2000 sec. 25p mode: 1/25 (OFF) sec., 1/50 sec., 1/60 sec., 1/120 sec., 1/250 sec., 1/500 sec., 1/1000 sec.
Synchro Scan Shutter:	60i/60p mode: 1/60.0 sec. to 1/250.0 sec. 30p mode: 1/30.0 sec. to 1/250.0 sec. 24p mode: 1/24.0 sec. to 1/250.0 sec. 50i/50p mode: 1/50.0 sec. to 1/250.0 sec. 25p mode: 1/25.0 sec. to 1/250.0 sec.
Slow Shutter Speed:	60i/60p mode: 1/15 sec., 1/30 sec. 30p mode: 1/15 sec. 24p mode: 1/12 sec. 50i/50p mode: 1/12.5, 1/12.5 sec. 25p mode: 1/12.5 sec.
Shutter Open Angle:	3.0 deg to 360.0 deg (in 0.5 deg steps, angle display)
Sensitivity:	NORMAL mode: F9 (2000 lx, 3200 K, 89.9% reflection, 1080/59.94i) F10 (2000 lx, 3200 K, 89.9% reflection, 1080/50i) HIGH SENS mode: F12 (2000 lx, 3200 K, 89.9% reflection, 1080/59.94i) F13 (2000 lx, 3200 K, 89.9% reflection, 1080/50i)
Minimum Subject Illumination:	Approx. 0.22 lx (HIGH SENS MODE, F1.4, +42 dB (S.GAIN))
Image S/N:	62 dB (standard)
Horizontal Resolution:	1000 TV or higher (center)

## Memory Card Recorder

Recording Media:	P2 card (for microP2 card: adaptor is required)
System Format:	1080/59.94i, 1080/23.98psF, 720/59.94p, 480/59.94i, 1080/50i, 720/50p, 576/50i
Recording Format:	AVC-Intra100/AVC-Intra50/AVC-LongG50/AVC-LongG25/AVC-LongG12/DVCPRO HD/DVCPRO50/DVCPRO/DV formats switchable
Recording Video Signal:	1080/59.94i, 1080/29.97pN, 1080/23.98pN, 720/59.94p, 720/29.97pN, 720/23.98pN, 480/59.94i, 480/29.97p, 1080/50i, 1080/25pN, 720/50p, 720/25pN, 576/50i, 576/25p
Recording/Playback Time*:	16GB × 1      32GB × 1      64GB × 1 AVC-Intra100: Approx. 16min.      Approx. 32min.      Approx. 64min. AVC-Intra50:      Approx. 32min.      Approx. 64min.      Approx. 128min. AVC-LongG50:      Approx. 32min.      Approx. 64min.      Approx. 128min. AVC-LongG25:      Approx. 64min.      Approx. 128min.      Approx. 256min. AVC-LongG12:      Approx. 120min.      Approx. 240min.      Approx. 480min. DVCPRO HD:      Approx. 16min.      Approx. 32min.      Approx. 64min. DVCPRO 50:      Approx. 32min.      Approx. 64min.      Approx. 128min. DVCPRO/DV:      Approx. 64min.      Approx. 128min.      Approx. 256min.

These are reference values for continuous recording using the Panasonic products. The recording time may differ depending on the scene or the number of clips.

## Digital Video

Sampling Frequency:	AVC-Intra100/AVC-LongG50/AVC-LongG25/AVC-LongG12/DVCPRO HD: Y: 74.1758 MHz, Pb/Pr: 37.0879 MHz (59.94 Hz) Y: 74.2500 MHz, Pb/Pr: 37.1250 MHz (50 Hz) DVCPRO50: Y: 13.5 MHz, Pb/Pr: 6.75 MHz DVCPRO: Y: 13.5 MHz, Pb/Pr: 3.375 MHz
Quantizing:	AVC-Intra100/AVC-Intra50/AVC-LongG50/AVC-LongG25: 10 bit AVC-LongG12/DVCPRO HD/DVCPRO50/DVCPRO/DV: 8 bit
Video Compression Format:	AVC-Intra100/AVC-Intra50: MPEG-4 AVC/H.264 Intra Profile AVC-LongG50/AVC-LongG25/AVC-LongG12: MPEG-4 AVC/H.264 DVCPRO HD/DVCPRO50/DVCPRO: DV-Based Compression DV: DV Compression

## Digital Audio

Recording Audio Signal:	AVC-Intra100/AVC-Intra50: 48 kHz/16 bit, 4CH and 48 kHz/24 bit, 4CH switch AVC-LongG50/AVC-LongG25: 48 kHz/24 bit, 4CH AVC-LongG12/DVCPRO HD/DVCPRO50/DVCPRO/DV: 48 kHz/16 bit, 4CH
Headroom:	18 dB/20 dB (switchable with menu)

## Proxy

Video Compression Format:	H.264/AVC Baseline Profile, H.264/AVC High Profile
Audio Compression Format:	AAC-LC, Linear PCM
Approx. Recording Time*:	AVC-G6 2CH MOV: Approx. 13 min. SHQ 2CH MOV: Approx. 25 min. HQ 2CH MOV: Approx. 78 min. LOW 2CH MOV: Approx. 135 min.

These are reference values for continuous recording using the Panasonic products. The recording time may differ depending on the scene or the number of clips.

## Video Input/Output

SDI OUT/IN (option):	BNC×1 1.5 G HD SDI: 0.8 V [p-p], 75 Ω SD SDI: 0.8 V [p-p], 75 Ω
MON OUT:	BNC×1 (Can be switched to HD SDI/SD SDI/analog composite on SmartUI.) 1.5 G HD SDI: 0.8 V [p-p], 75 Ω SD SDI: 0.8 V [p-p], 75 Ω Composite: 1.0 V [p-p], 75 Ω
HDMI OUT:	HDMI×1 (HDMI type A terminal, not compatible with VIERA Link)

## Audio Input/Output

Audio IN:	XLR (3 pin) × 2 LINE/MIC (switch selection) LINE: 0 dBu MIC: -50 dBu/-60 dBu (menu selection), +48 V ON/OFF (switch selection)
MIC IN:	XLR (3 pin) × 1, +48 V supported (selectable menu) -40 dBu/-50 dBu/-60 dBu (selectable menu)
Wireless IN:	25 pin, D-SUB, -40 dBu, 2CH supported
Audio OUT:	Pin jack × 2 (CH1, CH2), Output level: 600 Ω, 316 mV
Phones OUT:	3.5 mm diameter stereo mini jack × 1
Speaker:	20 mm diameter, round × 1

## Other Input/Output

GENLOCK IN:	BNC×1, 1.0 V [p-p], 75 Ω
TC IN/OUT:	BNC×1, IN/OUT switch selection IN: 0.5 V [p-p] to 8 V [p-p], 10 kΩ OUT: 2.0 ±0.5 V [p-p], Low impedance
DC IN:	XLR×1, 4 pin, DC 12 V (DC 11.0 V to 17.0 V)
DC OUT:	4 pin, DC 12 V (DC 11.0 V to 17.0 V), maximum output current 1.5 A
REMOTE:	10 pin
Lens:	12 pin
VF:	20 pin
LAN:	100BASE-TX/10BASE-T
USB2.0 (host):	Type A connector, 4 pin
USB2.0 (device):	Type B connector, 4 pin
USB2.0 (sub host):	Type A connector, 4 pin (exclusively for wireless module AJ-WM30)

## Included Accessories

### Shoulder strap, Mount cap

Weight and dimensions shown are approximate. Specifications are subject to change without notice.

\* Time shown above is when you record a series of 1 shot to a P2 card. Depending on numbers of shots you record, the time will get shorter than the number shown above.