



2-Port Hybrid™ KVM Switch with Audio

CS52A



Features

- One console (monitor, PS/2 keyboard, and USB mouse) controls two computers
- Remote Port Selector for convenient switch placement
- Supports multi-function mice
- USB 2.0 mouse port can be used for USB hub and USB peripheral sharing
- Compact design, built in all-in-one cables (console 0.15m; computers 0.6m, 1.2m)
- Audio (microphone and speaker) enabled -full bass response provides a rich experience for 2.1 surround sound systems
- Independent switching of the KVM and Audio focus - one computer can have the KVM focus while the other has the audio focus
- Superior video quality- up to 2048 x 1536; DDC2B
- Auto Scan function to monitor computer operation
- Non-powered



Specifications

Function	CS52A
Computer Connections	2
Port Selection	Hotkey, Remote Port Selector
Connectors	
Console Ports	1 x HDB-15 Female (Blue) 1 x 6-pin Mini-DIN Female (Purple) 1 x USB Type A Female 1 x 3.5mm Audio Jack Female (Green) 1 x 3.5mm Audio Jack Female (Pink)
KVM Ports	2 x HDB-15 Male (Blue) 2 x 6-pin Mini-DIN Male (Purple) 2 x USB Type A Male (Black) 2 x 3.5mm Audio Jack Male (Green) 2 x 3.5mm Audio Jack Male (Pink)
Remote Port Selector	1 x 2.5mm Audio Jack Female
LEDs	
Selected	2 (Green)
Cable Length	
Console	0.15 m
Computer	1 x 0.6 m; 1 x 1.2 m
Emulation	
Keyboard / Mouse	PS/2
Video	2048 x 1536; DDC2B
Scan Interval	3, 5, 10, 20 seconds (default: 5 secs.)
Power Consumption	DC5V: 0.25W
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.40 kg
Dimensions (L x W x H)	8.45 x 3.40 x 2.21 cm

Product information is subject to change without prior notice.

ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Publish Date: 02/2019 V5.0



© Copyright 2019 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.